

MKB Medical Services Defibrillator Cabinet Specification Sheet



Spec.

Dimensions: 400 x 400 x 200mm (HxWxD)

IP66 rated (water and dust ingress)

IK10 Impact Rating impact (highest achievable)

Material:

2mm mild steel, powder coated in any colour required (although yellow is standard) – our unique paint application process guarantees the paint will not peel in time unlike a lot of cabinets on the market

Heating:

50W convection heater controlled by a thermostat monitoring the temperature of the cabinet, ensuring the defibrillator remains at an environmentally stable condition at all times and is always ready to use

Lighting:

USB rechargeable LED strip light activated on opening of the door providing illumination inside the cabinet when required

Lock:

Marine grade lock, salt-spray tested for 1000 hours, providing an alpha-numerical code to open the latch lock through a full sized handle. Locking the cabinet just requires the door to be pushed shut.

A non-locking cabinet is also available which has a simple turn handle to open the cabinet. A key lock version is also available.

Warranty:

We are so confident in our cabinets that we offer a 10 year warranty on all cabinets sold, with 3 year warranty on the internal electrical system and a life time warranty offered on the lock by the lock manufacturer (terms and conditions apply) The 10 year warranty is applicable for cabinets purchased after 01/01/2019 and is subject to our Terms and Conditions.

Application:

Our cabinets are compatible with all makes and models of public defibrillators on the market